TS500

15" Multimedia TFT LCD Monitor

www.gnr.co.uk

Specifications

Key Features
25 ms response time
VESA Wall Mountable
Inegrated power supply

Monitor Colour
Black and silver

LCD
15" active matrix, thin film transistor (TFT)

Pixel Pitch
0.297(H) x 0.297(V)

Max. Resolution
XGA 1024x768

Scan Frequency
Horizontal: 31kHz - 60kHz
Vertical: 56Hz - 75Hz

View Angle
Horizontal: 120°
Vertical: 90°

Display Area (mm)
304.1(H) x 228.1(V)

Display Colour
16.7 million

Contrast Ratio
400:1

Brightness
270 cd/m2

Response Time (Tr+Tf)
25ms

Compatibility
Windows 95/98/98SE/Me/NT4/2000/XP
Mac OS, Macintosh
Plug & Play - DDC 2B

Input Video Signal (Connector: 15 pin D-sub)
Analogue 0.7 Vp-p separate sync.
TTL level, RGB analogue

AC/DC adapter:
Internal power supply

Input power source:
AC 100-240V, 50-60Hz

Power management
Normal operation: < 35 W
Off/Suspend/Stand-by mode: < 1.5 W

Operation Environment
Temperature: 0 - 40℃
Humidity: 20% - 80%

Tilt Angle
Max. forward tilt: 5°
Max. backward tilt: 20°

Dimensions (W x D x H)
340x354x162mm

EAN Code

Warranty
Three year on-site exchange

*Specifications are subject to change without notice

PGE Corporation Ltd
Unit 3, Newmarket Court, Kingston, Milton Keynes, MK10 0AG
Tel.: +44 (0)870 1280 880 / Fax: +44 (0)870 1280 878 / E-mail: sarah.wood@gnrintl.com
www.gnr.co.uk

Compliant with ISO-13406-2 regarding pixel faults. Specifications are subject to change without notice.